

# Firebreak 33 Fire Resistant Silicone Sealant

## PRODUCT DATA SHEET

## High flexibility with guaranteed fire security

Firebreak 33 is a one part fire resistant neutral curing silicone sealant with excellent acoustic performance. It is designed for internal or external use wherever flexible fire resistant and/or acoustic joints are required or to seal around pipe and cable service penetrations.



### Key features and benefits

- Independently tested to EN 1366-3: 2009 and EN 1366-4: 2006 providing up to 4 hours fire resistance
- Fire tested in conjunction with 100mm flexible partitions and concrete floors to offer a wide range of specifications
- Gap sizes up to 100mm & seals around metal pipes and cable bundle penetrations
- Low modulus: up to 25% movement in constant service conditions
- Maintains acoustic performance of substrate
- Excellent adhesion to most building substrates, including porous materials, without the use of primers
- Tested in conjunction with standard PE backing rod
- Non-toxic, low smoke, mould resistant and halogen free

- Good durability

- Quality assured including ISO 9001, CE Marking and independent third party product certification

### Typical applications

- Construction/movement joints in fire separating masonry and partition walls and concrete floors
- Acoustic joints at junctions of lightweight partitions with walls and floors
- Deflection joints between rigid walls or partitions and floor soffits
- Fire resistant glazing applications including curtain walls
- Service penetration seals to cables and metal pipes where they pass through fire resistant walls and floors
- Providing a cold smoke and acoustic seal to gaps around plastic pipes prior to the fitting of Firebreak FX Series Pipe Collars
- Bedding of fire grills etc., when fitted to uneven services

Since the product is applied under circumstances beyond our control, Neutron Fire Technologies Limited can accept no direct or consequential liability whether in contract or in tort, for the interpretations of such recommendations and reserves the right to modify the recommendations as necessary.

### Testing and certification

- Extensive testing to EN 1366-3: 2009 and EN 1366-4: 2006 providing up to 4 hours fire resistance to linear gaps and service penetrations
- Zero flame spread when tested to EN ISO 11923-2: 2010 giving Class E classification to EN 13501-1:2007 + A1
- Classification to EN 13501 and CE Mark (ETA 21/0223 & 21/0221)
- Mechanical and durability testing to EAD 350454-00-1104 & EAD 350141-00-1106
- Third party product certification with UL International (Certificate # UL-EU-00708)
- Acoustic testing to EN ISO 140: Part 3: 1995 sealing multiple gaps in a Rw 54 dB rated acoustic partition with no loss of acoustic performance



CE
2821
21
2821-CPR-0118
ETA 21/0221 & ETA 21/0223
EAD 350454-00-1104 & EAD 350141-00-1106